

QUICK DISCONNECTS

Parker Brass Quick Connect Sockets

- ◆ Brass Sockets
- ◆ 4:1 Safety Factor
- ◆ Buna-N O-rings standard
- ◆ 250° F Max.
- ◆ ST Series (Straight-Thru)
- ◆ 1/8" 2500 PSI
- ◆ 1/4" 5200 PSI
- ◆ 3/8" 2700 PSI
- ◆ 1/2" 2200 PSI
- ◆ 3/4" 1700 PSI



F x F



M x F

		Each
W04-14114-A	1/8" F x 1/8" MPT	6.50
W04-14214-A	1/8" F x 1/8" FPT	6.10
W04-24124-A	1/4" F x 1/4" MPT	7.40
W04-24224-A	1/4" F x 1/4" FPT	7.40
W04-34134-A	3/8" F x 3/8" MPT	8.60
W04-34234-A	3/8" F x 3/8" FPT	8.50
W04-54154-A	1/2" F x 1/2" MPT	14.70
W04-54254-A	1/2" F x 1/2" FPT	14.30
W04-74174-A	3/4" F x 3/4" MPT	22.80
W04-74274-A	3/4" F x 3/4" FPT	37.60

Parker Zinc Quick Connect Plugs

- ◆ Zinc Plated Steel Plugs
- ◆ 4:1 Safety Factor
- ◆ 250° F Max.
- ◆ ST Series (Straight-Thru)
- ◆ 1/8" 2500 PSI
- ◆ 1/4" 5200 PSI
- ◆ 3/8" 2700 PSI
- ◆ 1/2" 2200 PSI
- ◆ 3/4" 1700 PSI



M x F



M x M

		Each
W04-11114-B	1/8" M x 1/8" MPT	6.80
W04-21124-B	1/4" M x 1/4" MPT	2.70
W04-21224-B	1/4" M x 1/4" FPT	2.70
W04-31134-B	3/8" M x 3/8" MPT	2.80
W04-31234-B	3/8" M x 3/8" FPT	2.90
W04-51154-B	1/2" M x 1/2" MPT	7.80
W04-51254-B	1/2" M x 1/2" FPT	8.50
W04-71174-B	3/4" M x 3/4" MPT	29.90
W04-71274-B	3/4" M x 3/4" FPT	28.50

Parker S. S. Quick Connect Sockets

- ◆ Stainless Steel Sockets
- ◆ 4:1 Safety Factor
- ◆ Buna-N O-rings standard
- ◆ 303 SS
- ◆ 250° F Max.
- ◆ ST Series (Straight-Thru)
- ◆ 1/8" 4200 PSI
- ◆ 1/4" 6700 PSI
- ◆ 3/8" 5500 PSI
- ◆ 1/2" 3000 PSI



F x F



M x F

		Each
W04-13214-A	1/8" F x 1/8" FPT	58.50
W04-23224-A	1/4" F x 1/4" FPT	79.70
W04-33134-A	3/8" F x 3/8" MPT	91.00
W04-33234-A	3/8" F x 3/8" FPT	85.90
W04-53154-A	1/2" F x 1/2" MPT	128.40
W04-53254-A	1/2" F x 1/2" FPT	94.50

Parker S. S. Quick Connect Plugs

- ◆ Stainless Steel Plugs
- ◆ 4:1 Safety Factor
- ◆ 303 SS
- ◆ 250° F Max.
- ◆ ST Series (Straight-Thru)
- ◆ 1/4" 6700 PSI
- ◆ 3/8" 5500 PSI
- ◆ 1/2" 3000 PSI



M x F



M x M

		Each
W04-23124-B	1/4" M x 1/4" MPT	24.80
W04-23224-B	1/4" M x 1/4" FPT	26.10
W04-33134-B	3/8" M x 3/8" MPT	32.90
W04-33234-B	3/8" M x 3/8" FPT	32.30
W04-53154-B	1/2" M x 1/2" MPT	50.10
W04-53254-B	1/2" M x 1/2" FPT	46.60

GP Brass Quick Connect Sockets

- ◆ Brass Sockets
- ◆ 1/4" = 4:1 Safety Factor
- ◆ 3/8" = 4:1 Safety Factor
- ◆ Viton O-rings standard
- ◆ 250° F Max.
- ◆ Straight-Thru Series
- ◆ 1/4" 5000 PSI
- ◆ 3/8" 4000 PSI



F x F



M x F

		Each
W04-24125-A	1/4" F x 1/4" MNPT	4.40
W04-24225-A	1/4" F x 1/4" FNPT	4.40
W04-34135-A	3/8" F x 3/8" MNPT	5.40
W04-34155-A	3/8" F x 1/2" MNPT	5.90
W04-34235-A	3/8" F x 3/8" FNPT	5.40

GP Hardened Steel, Brass Plated Quick Connect Plugs

- ◆ Hardened Steel, Brass Plated Plugs
- ◆ 4:1 Safety Factor
- ◆ Straight-Thru Series
- ◆ 250° F Max.
- ◆ 1/4" 5000 PSI
- ◆ 3/8" 4000 PSI



M x F



M x M

		Each
W04-21125-B	1/4" M x 1/4" MNPT	2.10
W04-21225-B	1/4" M x 1/4" FNPT	2.50
W04-31135-B	3/8" M x 3/8" MNPT	1.70
W04-31235-B	3/8" M x 3/8" FNPT	2.50

QUICK DISCONNECTS

GP S. S. Quick Connect Plugs


- ◆ Stainless Steel Plugs
- ◆ 4:1 Safety Factor
- ◆ 416 SS Heat Treated
- ◆ 250° F Max.
- ◆ Straight-Thru Series
- ◆ 1/4" 5500 PSI
- ◆ 3/8" 5000 PSI



		Each
W04-23125-B	1/4" M x 1/4" MNPT	3.90
W04-23225-B	1/4" M x 1/4" FNPT	4.70
W04-33135-B	3/8" M x 3/8" MNPT	4.80
W04-33235-B	3/8" M x 3/8" FNPT	5.60

Hansen Brass Quick Connect Sockets


- ◆ Brass Sockets
- ◆ 4:1 Safety Factor
- ◆ Buna-N O-rings standard
- ◆ 250° F Max.
- ◆ ST Series (Straight-Thru)
- ◆ 1/8" 3400 PSI
- ◆ 1/4" 5500 PSI
- ◆ 3/8" 4200 PSI
- ◆ 1/2" 3500 PSI
- ◆ 3/4" 2100 PSI



		Each
W04-14112-A	1/8" F x 1/8" MPT	10.30
W04-14212-A	1/8" F x 1/8" FPT	10.30
W04-24122-A	1/4" F x 1/4" MPT	7.90
W04-24222-A	1/4" F x 1/4" FPT	7.70
W04-34132-A	3/8" F x 3/8" MPT	7.90
W04-34232-A	3/8" F x 3/8" FPT	7.80
W04-54152-A	1/2" F x 1/2" MPT	12.80
W04-54252-A	1/2" F x 1/2" FPT	12.80
W04-74172-A	3/4" F x 3/4" MPT	34.10
W04-74272-A	3/4" F x 3/4" FPT	30.30

Hansen Zinc Quick Connect Plugs


- ◆ Zinc Plated Steel Plugs
- ◆ 4:1 Safety Factor
- ◆ 250° F Max.
- ◆ ST Series (Straight-Thru)
- ◆ 1/8" 3400 PSI
- ◆ 1/4" 5500 PSI
- ◆ 3/8" 4200 PSI
- ◆ 1/2" 3500 PSI
- ◆ 3/4" 2100 PSI



		Each
W04-11112-B	1/8" M x 1/8" MPT	5.60
W04-21122-B	1/4" M x 1/4" MPT	2.40
W04-21222-B	1/4" M x 1/4" FPT	2.40
W04-31132-B	3/8" M x 3/8" MPT	2.80
W04-31232-B	3/8" M x 3/8" FPT	2.80
W04-51152-B	1/2" M x 1/2" MPT	6.10
W04-51252-B	1/2" M x 1/2" FPT	8.30
W04-71172-B	3/4" M x 3/4" MPT	12.50
W04-71272-B	3/4" M x 3/4" FPT	15.90

Hansen S.S. Quick Connect Plugs


- ◆ Stainless Steel Plugs
- ◆ 4:1 Safety Factor
- ◆ 303 SS
- ◆ 250° F Max.
- ◆ ST Series (Straight-Thru)
- ◆ 1/4" 7500 PSI
- ◆ 3/8" 6300 PSI
- ◆ 1/2" 3600 PSI



		Each
W04-23122-B	1/4" M x 1/4" MPT	6.30
W04-23222-B	1/4" M x 1/4" FPT	7.60
W04-33132-B	3/8" M x 3/8" MPT	8.60
W04-33232-B	3/8" M x 3/8" FPT	10.30
W04-53152-B	1/2" M x 1/2" MPT	18.80
W04-53252-B	1/2" M x 1/2" FPT	20.60

Hansen S.S. Quick Connect Sockets

- ◆ Stainless Steel Sockets
- ◆ 4:1 Safety Factor
- ◆ Buna-N O-rings standard
- ◆ 303 SS
- ◆ 250° F Max.
- ◆ ST Series (Straight-Thru)
- ◆ 1/8" 4200 PSI
- ◆ 1/4" 7500 PSI
- ◆ 3/8" 6300 PSI
- ◆ 1/2" 3600 PSI



		Each
W04-23222-A	1/4" F x 1/4" FPT	30.40
W04-33132-A	3/8" F x 3/8" MPT	45.40
W04-33232-A	3/8" F x 3/8" FPT	34.80
W04-53152-A	1/2" F x 1/2" MPT	46.10
W04-53252-A	1/2" F x 1/2" FPT	42.80

QUICK DISCONNECTS/SOCKET O-RINGS

Foster S. S. Quick Connect Sockets

- ◆ Stainless Steel Sockets
- ◆ 4:1 Safety Factor
- ◆ Buna-N O-rings standard
- ◆ 303 SS
- ◆ 250° F Max.
- ◆ FST Series (Straight-Thru)
- ◆ 1/8" 4200 PSI
- ◆ 1/4" 5000 PSI
- ◆ 3/8" 5500 PSI
- ◆ 1/2" 3000 PSI




FXF

		Each
W04-13211-A	1/8" F x 1/8" FPT	27.80
W04-23221-A	1/4" F x 1/4" FPT	27.50
W04-33231-A	3/8" F x 3/8" FPT	34.60
W04-53251-A	1/2" F x 1/2" FPT	55.70

Foster S. S. Quick Connect Plugs

- ◆ Stainless Steel Plugs
- ◆ 4:1 Safety Factor
- ◆ 303 SS
- ◆ 250° F Max.
- ◆ FST Series (Straight-Thru)
- ◆ 1/4" 5000 PSI
- ◆ 3/8" 5500 PSI
- ◆ 1/2" 3000 PSI



M x F

M x M

		Each
W04-23121-B	1/4" M x 1/4" MPT	7.10
W04-23221-B	1/4" M x 1/4" FPT	9.20
W04-33131-B	3/8" M x 3/8" MPT	10.30
W04-33231-B	3/8" M x 3/8" FPT	12.00
W04-53151-B	1/2" M x 1/2" MPT	17.90
W04-53251-B	1/2" M x 1/2" FPT	17.90

Foster Brass Quick Connect Sockets

- ◆ Brass Sockets
- ◆ 4:1 Safety Factor
- ◆ Buna-N O-rings standard
- ◆ 250° F Max.
- ◆ FST Series (Straight-Thru)
- ◆ 1/8" 2600 PSI
- ◆ 1/4" 5500 PSI
- ◆ 3/8" 3500 PSI
- ◆ 1/2" 2700 PSI
- ◆ 3/4" 2700 PSI



FXF



M x F

		Each
W04-14111-A	1/8" F x 1/8" MPT	5.60
W04-14211-A	1/8" F x 1/8" FPT	5.60
W04-24121-A	1/4" F x 1/4" MPT	6.40
W04-24221-A	1/4" F x 1/4" FPT	6.00
W04-34131-A	3/8" F x 3/8" MPT	6.50
W04-34231-A	3/8" F x 3/8" FPT	7.00
W04-54151-A	1/2" F x 1/2" MPT	12.30
W04-54251-A	1/2" F x 1/2" FPT	12.00
W04-74171-A	3/4" F x 3/4" MPT	20.30
W04-74271-A	3/4" F x 3/4" FPT	20.30

Foster Zinc Quick Connect Plugs

- ◆ Zinc Plated Steel Plugs
- ◆ 4:1 Safety Factor
- ◆ 250° F Max.
- ◆ FST Series (Straight-Thru)
- ◆ 1/8" 2600 PSI
- ◆ 1/4" 5500 PSI
- ◆ 3/8" 3500 PSI
- ◆ 1/2" 2700 PSI
- ◆ 3/4" 2700 PSI



M x F

M x M

		Each
W04-11111-B	1/8" M x 1/8" MPT	2.00
W04-21121-B	1/4" M x 1/4" MPT	1.90
W04-21221-B	1/4" M x 1/4" FPT	2.20
W04-31131-B	3/8" M x 3/8" MPT	2.30
W04-31231-B	3/8" M x 3/8" FPT	2.40
W04-51151-B	1/2" M x 1/2" MPT	5.40
W04-51251-B	1/2" M x 1/2" FPT	6.40
W04-71171-B	3/4" M x 3/4" MPT	7.70
W04-71271-B	3/4" M x 3/4" FPT	8.90

Buna-N or Viton O-Rings

- ◆ C = Buna-N to 250° F
- ◆ V = Viton to 300° F + & for aggressive chemicals
- ◆ Fits: Foster, General Pump, Hansen, JE Adams, Parker
- ◆ ST or FST straight thru series only, Buna-N: Black, Viton: Brown



Viton

Buna-N

		Each
W02-00061-C	1/8" QC	.40
W02-00061-V	1/8" QC	1.40
W02-00063-C	1/4" QC	.40
W02-00063-V	1/4" QC	.70
W02-00067-C	3/8" QC	.40
W02-00067-V	3/8" QC	.90
W02-00071-C	1/2" QC	.90
W02-00071-V	1/2" QC	1.80
W02-00074-C	3/4" QC	1.00
W02-00074-V	3/4" QC	2.00

Buna-N or Viton O-Rings 25/Package

- ◆ C = Buna-N to 250° F
- ◆ V = Viton to 300° F + and for aggressive chemicals
- ◆ Fits: Foster, General Pump, Hansen, JE Adams, Parker
- ◆ ST or FST straight thru series only, Buna-N: Black, Viton: Brown

Package Qty.



Viton

Buna-N

		Each
W02-00061-C1	1/8" QC - 25/Pkg.	7.20
W02-00061-V1	1/8" QC - 25/Pkg.	19.30
W02-00063-C1	1/4" QC - 25/Pkg.	7.90
W02-00063-V1	1/4" QC - 25/Pkg.	14.20
W02-00067-C1	3/8" QC - 25/Pkg.	8.80
W02-00067-V1	3/8" QC - 25/Pkg.	19.30
W02-00071-C1	1/2" QC - 25/Pkg.	9.80
W02-00071-V1	1/2" QC - 25/Pkg.	32.40
W02-00074-C1	3/4" QC - 25/Pkg.	19.30
W02-00074-V1	3/4" QC - 25/Pkg.	39.40