

Xtreme Performance Fuel Filter

- ◆ 1/4" F x F
- ◆ 10 Micron filtration
- ◆ Plastic bowl
- ◆ Easy to drain water/ sediment bowl
- ◆ Convenient spin-on type
- ◆ Xtreme Performance



		Each
V04-00308	Fuel Filter	62.70
V04-00308-01	Filter Element w/o-ring & gasket	26.50
V04-00308-03	Gasket	10.60
V04-00308-04	Vent Plug Ass'y	9.60
V04-00308-05	O-ring	10.10
V04-00308-07	Drain Ass'y	7.70
V04-00308-K	Replacement Bowl Kit	37.10

Fuel Filter

- ◆ 1/4" F x F
- ◆ SS 120 Mesh
- ◆ Clear plastic bowl for easy viewing
- ◆ Aluminum housing

Try this cost effective filter!



		Each
V04-00311	Fuel Filter	19.90
V04-00311-1	Filter Element	9.50

Fuel Filter - Plastic

- ◆ Inline - disposable
- ◆ 1/4" In/Out
- ◆ Plastic



		Each
07-02500	Fuel Filter	2.60

In-Line Filter - Green Cap



- ◆ 5.8 GPM @ 145 PSI
- ◆ 1/2" M x 1/2" F
- ◆ (2) 1/4" F accessory side ports
- ◆ 176° F
- ◆ Material: Aluminum, Brass, Plastic, Buna-N
- ◆ 40 Mesh



		Each
C04-00141	Inline Water Filter - #ZMFIL	27.30
C04-00141-1	Green Cap	12.20
C04-00141-03	Filter Screen	13.00
C07-01421	O-ring for C04-00141-1	1.30

In-Line High Pressure Filter

- ◆ 8 GPM flow rate
- ◆ 5000 PSI max. pressure
- ◆ 300° F
- ◆ Recommended for use with rotating nozzles



		Each
J06-00271A	1/4" F x 1/4" M - Brass w/ZPS FNPT	13.80
J06-00271B	1/4" QC x 1/4" M - Brass w/ZPS QC	22.60
J06-00271A-1	Replacement O-ring	3.40
J06-00271A-2	Replacement Screen	4.10
J06-00271A-3	Replacement Inner Screen Support	5.40

In-Line High Pressure Filter



- ◆ 8 GPM flow rate
- ◆ 5500 PSI max. pressure
- ◆ 1/4" QC x 1/4" M
- ◆ SS QC w/brass Male threads
- ◆ 350° F
- ◆ Recommended for use with rotating nozzles
- ◆ General filter



		Each
J06-00271C	In-Line High Pressure Filter	22.40

FILTERS/SCREENS/Y-STRAINERS

Soap Screen - Brass

- ◆ 1/4" Hose barb
- ◆ 50 Mesh stainless steel screen
- ◆ Removable mesh for easy cleaning



		Each
C04-00131	Soap Screen - Spring loaded with check valve	4.60

Soap Screen - Plastic

- ◆ 1/4" Hose barb
- ◆ Corrosion resistant plastic



		Each
C04-00130	Soap Screen - Spring loaded with check valve	1.30
C04-00129	Soap Screen - w/o check valve	1.30

Soap Screen - Stainless Steel

- ◆ 1/4" Barb
- ◆ Nickel plated brass body
- ◆ SS 60 mesh screen
- ◆ SS check ball



		Each
C04-00135	Soap Screen	13.00

Suction-Line Strainers/Tank Screens

- ◆ SS Screen
- ◆ Black PVC base: C04-00110
- ◆ Yellow PVC base: C04-00120
- ◆ Threaded to attach to pipe or nipple
- ◆ Use for pump or chemical suction



		Each
C04-00110	3/8" Female - 30 Mesh	4.20
C04-00120	1/2" Female - 30 Mesh	3.40

DuraView Inlet Filters

- ◆ 8 GPM @ 180° F
- ◆ 150 PSI max. pressure
- ◆ 60 Mesh
- ◆ Materials: Brass, SS, Buna-N
- ◆ Strongest see-through filter on the market
- ◆ Load bearing brass spine
- ◆ Integrated garden hose connector
- ◆ Flow through design
- ◆ Clear plastic cover



		Each
C04-00144	1/2" M x GH - #100649	27.60
C04-00145	3/8" M x GH - #100650	27.60
C04-00146	1/2" M x GH, 1/4" F Bypass - #100651	32.00
C04-00147	3/8" M x GH, 1/4" F Bypass - #100652	32.00
C04-00148	Repair Kit - Includes screen & o-rings - #100669	5.60

Garden Hose Washers

- ◆ PVC base
- ◆ Filter washer SS 30-30 mesh screen



		Each
C04-00121	Filter Washer - #FWG3030	0.60
C05-00271	Hose Washer - 5/8" ID x 1" OD	0.40

Y-Strainer - Inline Cast Iron

- ◆ 400 PSI (WOG)
- ◆ 250 PSI (WSP)
- ◆ 1" F x F
- ◆ 406° F
- ◆ SS 20 mesh screen



		Each
E22-00003	Y-Strainer - #77S	44.10

Y-Strainer - Inline Plastic

- ◆ 21 GPM flow rate
- ◆ 145 PSI max. pressure
- ◆ 3/4" F x F
- ◆ 104° F
- ◆ SS 50 mesh screen



		Each
C04-00140	Y-Strainer - #FY34	44.40

Y-Strainer - Inline Bronze

- ◆ 300 PSI (WOG)
- ◆ 150 PSI (WSP)
- ◆ 3/4" F x F
- ◆ 304SS 20 mesh screen



		Each
E22-00013	Y-Strainer	61.90