

XTREME PERFORMANCE PRESSURE WASHER SERIES

XTREME



XTREME PERFORMANCE PRESSURE WASHER SERIES



BUILT AND DESIGNED FOR THOSE WHO DEMAND THE HIGHEST PERFORMANCE. THE XTREME SERIES COMBINES THE DESIGN & ENGINEERING, HIGHEST QUALITY MATERIALS, AND UNCOMPROMISING CRAFTSMANSHIP TO CREATE A PRESSURE WASHER THAT TAKES EVERY STANDARD OF THE INDUSTRY AND BLASTS IT OUT OF THE WATER!

STANDARD FEATURES:

- Pressure atomizing burner coupled with a cold water wrap coil and schedule 80 steel pipe for a long lasting, highly efficient heating system
- Oil bath type pumps designed for rugged use and long life
- Precise chemical metering
- Stainless steel float tank
- Rotary electrical switches
- Enclosed stainless steel control panel
- High quality single phase motor with dual capacitors
- Ball bearing pneumatic wheels
- Easy access fuel tank with replaceable filter
- Safety relief valve
- Heavy steel and stainless steel construction
- 50 ft. of wire braid hose and trigger wand
- Fuel solenoid for positive oil shut off
- Temperature control - variable from 32° to 200°

MODEL	2162AE-X	2162-X	3112-X	3202-X	4182-X	4302-X	5182-X
CAPACITY*	2.1 GPM	2.1 GPM	3 GPM	3 GPM	4 GPM	4 GPM	4.8 GPM
PRESSURE*	1600 PSI	1600 PSI	1100 PSI	2000 PSI	1800 PSI	3000 PSI	1800 PSI
PUMP	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath
MOTOR**	2.3 HP, 115 V, 1 PH	2.3 HP, 115 V, 1 PH	2.3 HP, 115 V, 1 PH	4 HP, 230 V, 1 PH	5 HP, 230 V, 1 PH	8 HP, 230 V, 1 PH	6 HP, 230 V, 1 PH
COIL*** (STEEL PIPE)	95', 1/2" ID Schedule 80	126', 1/2" ID Schedule 80	126', 1/2" ID Schedule 80	126', 1/2" ID Schedule 80	170', 1/2" ID Schedule 80	170', 1/2" ID Schedule 80	170', 1/2" ID Schedule 80
BURNER, PRESSURE ATOMIZING AUTO IGNITION	Kero, #1 Dsl 170,000 BTU	Kero, #1 Dsl 200,000 BTU	Kero, #1 Dsl 315,000 BTU	Kero, #1 Dsl 315,000 BTU	Kero, #1 Dsl 434,000 BTU	Kero, #1 Dsl 434,000 BTU	Kero, #1 Dsl 560,000 BTU
FUEL CONSUMPTION TANK CAPACITY	1.22 GPH 6 GAL	1.4 GPH 12 GAL	2.25 GPH 12 GAL	2.25 GPH 12 GAL	3.1 GPH 14 GAL	3.1 GPH 14 GAL	4.0 GPH 14 GAL
CHEMICAL	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
FLOAT TANK	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
TEMPERATURE CONTROL & SOLENOID	Standard	Standard	Standard	Standard	Standard	Standard	Standard
STEAM CAPACITY (OPTIONAL)	N/A	60 GPH	90 GPH	90 GPH	120 GPH	120 GPH	150 GPH
WHEELS	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic
DIMENSIONS	L-30 1/2" H-33" W-25"	L-34" H-42" W-27 1/2"	L-34" H-42" W-27 1/2"	L-34" H-42" W-27 1/2"	L-35" H-45" W-29 1/2"	L-35" H-45" W-29 1/2"	L-35" H-46 1/2" W-29 1/2"
WEIGHT	340 LBS	400 LBS	400 LBS	420 LBS	450 LBS	590 LBS	575 LBS

NOTE: All 115 VOLT models have ground fault interrupters standard. Available UL approved.
 *Gallage and pressure may vary + or - 5% due to manufacturing tolerances in components.
 **Special voltages upon request. Gallonages and pressures may be less on 3 phase current.
 ***ASTM A-53 steel pipe, spiral wound, cold water wrap design, removable.

ENGLISH TO METRIC CONVERSION CHART

1 gallon/minute = 3.78 liters/minute
 1 foot = .3048 meters
 1 horsepower = .746 kilowatts
 1 inch = 2.54 centimeters
 100 PSI = 7.03 Kg/cm²
 1 pound = .45359 kilograms

2.1 GPM TO 4.8 GPM
 1600 PSI TO 3000 PSI



Model # XP-03-03. Printed in the U.S.A.

1.800.255.6823 www.alkota.com