

# Steam Cleaners



OLD VALUES. NEW IDEAS.



With 300° steam,  
Alkota's Steam Cleaners  
are unbeatable when it  
comes to melting away  
grease and grime.



**MODEL 122**  
PORTABLE  
GENERAL PURPOSE



**MODEL 201**  
HEAVY DUTY GAS FIRED



**MODEL 240**  
HEAVY DUTY OIL FIRED

## HEAVY DUTY STEAM CLEANERS

- 300° steam that rids baked on grease.
- Fired by diesel, natural gal or LP gas
- Oil fired models can be easily moved with ball bearing pneumatic wheels

- Gas fired units are designed for permanent installations
- Models 3854 and 3854-2 are combination steam cleaners and high pressure washers
- Perfect for auto and truck repair shops, barrel and tanker cleaning, heavy construction, roof thawing and vehicle restoration

## SPECIFICATIONS

MODEL	120	122	240	181	241	301
STEAM CAPACITY*	120 GPH	120 GPH	240 GPH	180 GPH	240 GPH	300 GPH
WASH CAPACITY*	N/A	N/A	N/A	N/A	N/A	N/A
STEAM PRESSURE*	325 PSI	400 PSI	400 PSI	250 PSI	250 PSI	400 PSI
WASH PRESSURE*	N/A	N/A	N/A	N/A	N/A	N/A
PUMP	Twin Piston, Positive Displacement	Duplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath	Triplex, Oil Bath
MOTOR**	¾ HP, 115 V, 1 PH	¾ HP, 115 V, 1 PH	2 HP, 115 V, 1 PH	¾ HP, 115 V, 1 PH	2 HP, 115 V, 1 PH	4 HP, 230 V, 1 PH
(STEEL PIPE) COIL***	126', ¾" ID, Schedule 40	126', ¾" ID, Schedule 40	245', ¾" ID, Schedule 40	243', ¾" ID, Schedule 40	420', ¾" ID, Schedule 40	515', ¾" ID, Schedule 40
BURNER, OIL, PRESSURE, ATOMIZING, AUTO, IGNITION	Kerosene, #1 or #2 Diesel 392,000 BTU	Kerosene, #1 or #2 Diesel 392,000 BTU	Kerosene, #1 or #2 Diesel 784,000 BTU	N/A	N/A	N/A
BURNER, GAS, NATURAL, ASPIRATING, NAT. OR L.P. GAS	N/A	N/A	N/A	490,000 BTU	650,000 BTU	1,040,000 BTU
FUEL CONSUMPTION	2.80 GPH	2.80 GPH	5 GPH	Nat.-.467 Cu. Ft. per Hr. L.P.-5.3 GPH	Nat.-.620 Cu. Ft. per Hr. L.P.-7 GPH	Nat.-.990 Cu. Ft. per Hr. L.P.-11.3 GPH
TANK CAPACITY	Fuel 9 Gal.	Fuel 12 Gal.	Fuel 10 Gal.	N/A	N/A	N/A
WAND	Open-Standard	Open-Standard	Open-Standard	Open-Standard	Open-Standard	Trigger-Standard
HOSE	¾" x 50"	¾" x 50"	¾" x 50"	¾" x 50"	¾" x 50"	¾" x 50"
CHEMICAL	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
FLOAT TANK	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
TEMPERATURE CONTROL	Standard	Standard	Standard	Standard	Standard	Standard
WHEELS	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	10" Ball Bearing Pneumatic	N/A	N/A	N/A
DIMENSIONS	L-55" H-41" W-27"	L-34" H-42" W-27½"	L-57" H-45" W-29"	L-48" H-54" W-22½"	L-50" H-61" W-24"	L-56" H-71" W-30"
WEIGHT	350 lbs.	400 lbs.	525 lbs.	600 lbs.	780 lbs.	905 lbs.

\* GALLONAGE AND PRESSURE MAY VARY ± 5% DUE TO MANUFACTURING TOLERANCES IN COMPONENTS.

\*\* SPECIAL VOLTAGES UPON REQUEST. GALLONAGES AND PRESSURES MAY BE LESS ON 3 PHASE CURRENT.

\*\*\* ASTM A-53 STEEL PIPE, SPIRAL WOUND, COLD WATER WRAP DESIGN, REMOVABLE.



OLD VALUES. NEW IDEAS.

### ENGLISH TO METRIC CONVERSION CHART

1 GALLON/MINUTE = 3.78 LITERS/MINUTE  
 1 HORSEPOWER = .746 KILOWATTS  
 100 PSI = 7.03 KG/CM2  
 1 FOOT = .3048 METERS  
 1 INCH = 2.54 CENTIMETERS  
 1 POUND = .45359 KILOGRAMS

Alcester, South Dakota 57001  
 1.800.255.6823 www.alkota.com



Form # SC-07-02. Printed in the U.S.A.